

CS-C850D Specifications

BASIC SPECIFICATIONS:

Configuration:	Digital Color Copier/MFP with Standard Duplex, 500 Sheet Paper Drawer Plus 150 Sheet Multi-Purpose Tray, Optional Network Printing, Scanning, and Faxing.
Resolution:	Multi Bit 600 DPI
Copier Memory:	Standard 256MB RAM, 20GB Hard Disk Drive
Magnification:	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, 25-400% Zoom
Electrical Requirements:	120V, 60Hz, 12A
Dimensions:	23.2"W x 23"D x 34.3"H
Weight:	262.3 lbs
Max. Monthly Volume (Color / Mono):	25,000 / 100,000 Pages per Month

OUTPUT SPEEDS:

Warm-Up Time:	Within 180 Seconds, Program and Scan During Warmup, Auto Start
First Copy Out (Color / Mono):	24.5 / 10.8 Seconds
First Print Out (Color / Mono):	28.0 / 17.0 Seconds
Pages Per Minute (Color / Mono):	8 / 31 Letter, 4 / 15 Legal, 4 / 15 Ledger

PAPER SUPPLY:

Standard Paper Sources:	500 Sheet Drawer, 150 Sheet MPT
Drawer Paper Size:	8.5" x 11" / 11" x 17"
MPT Paper Size:	3.1" x 5.8" - 12" x 18"
Std / Max Paper Capacity:	650 / 1,150
Paper Weight:	16-24 lb Bond via Paper Drawers, 16 lb Bond -121 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text & Photo, Print, Map, ECO
Continuous Copy:	Up to 999, Auto Reset to 1
Additional Features:	Gloss Mode, Positive / Negative Reverse, Mirror Image, Rotate Copy, Transparency Mode, Border Erase, X/Y Border Erase, Electronic Sort, Rotate Sort, Full-Color & Monochrome copy sets in same run, Split Copy, Margin Shift, Dual Access, Signature Booklet Making, XY-Zoom, Memo Mode, Job Management: Job Interrupt, Job Build, 8 Job Programs, Repeat Copy, 500 Department Management Codes, Color Adjustment: OneTouch, Color Balance -11 levels, Hue, Auto Exposure - 7 or 13 levels, 6 Monotone Colors, Manual Exposure - 7 or 13 levels, Auto GrayScale, Sharpness - 6 levels, Color Calibration

DUPLEX UNIT:

Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16-24 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book:2, 2:1

PAPER HANDLING OPTIONS:

DOCUMENT PROCESSOR: SRDF-2

Type:	Reversing Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size
Capacity:	100 Sheet RADF/ 31 Letter Size Originals per Minute
Paper Weight:	9-42 lb Bond
Dimensions / Weight:	21.8"W x 18.8"D x 5.4"H / 23.1 lbs

FINISHER: DF-35

Stack Capacity:	Main Tray: 3,000 Sheets; Sub Tray: 250 Sheets
Paper Size:	Main: 8.5" x 11" - 11" x 17"; Sub: 5.5" x 8.5" - 12" x 18"
Paper Weight:	16 lb Bond - 121 lb Index
Staple Capacity:	50 Sheets: 5.5" x 8.5", 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	3 Positions: Top Left, Bottom Left, Two Position Side
Punch:	Standard 2 and 3 Hole
Dimensions / Weight:	27.4"W x 23.6"D x 39.75"H / 110.1 lbs

DUAL PAPER DRAWER: PF-35

Paper Capacity:	2 x 250 Sheets
Paper Weight:	16-24 lb Bond
Paper Size:	8.5" x 11" - 11" x 17"
Dimensions / Weight:	22"W x 22.3"D x 7.8"H / 35.3 lbs

CONNECTIVITY OPTIONS:

PRINT: PRINT SYSTEM (S)

Controller:	Embedded PowerPC750/ 400 MHz Controller
Printer Memory:	Standard 128MB, Upgradeable to 640MB via 100 Pin DIMMs. Optional Printer HDD. Standard CF Card Slot (Type 1)
Supported PDL / Emulations:	PRESCRIBE, KPDL3 (PS3), PCL 6 (PCL 5c, PCL XL), KC-GL (HP-GL)
Fonts:	136 Outline Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/Me/NT4.x/2000/XP
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100 BaseTX, Full-Speed USB2.0, Bi-Directional Parallel IEEE1284
KUIO LV Expansion Slot (2):	1st Slot for Optional Hard Disk Drive, 2nd Slot for Optional: IB-11 Serial RS-232C; IB-20 10/100 BaseTX, 10Base2; or IB-22 Enhanced Wireless NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, KM-NET Job Manager, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

PRINTER HARD DISK DRIVE:

Enables Document Printing and e-MPS Functions: Private Print, Job Storage, Quick Copy, Proof and Hold, Virtual MailBoxes, BarCode

SCAN: SCAN SYSTEM (C)

Resolution:	200, 300, 400, 600 DPI
Scan Speed (Color / Mono):	Up to 20 / 31 Sheets Per Minute
File Formats:	PDF, TIFF, JPEG
Connectivity:	Standard NS-30 10/100BaseTX
Supported Protocol:	TCP/IP
Scanning Features:	KM Document Flow System - Document Management System, Scan to PC/File, Scan to Mac, Scan to E-Mail, TWAIN
Driver:	TWAIN Driver
Utilities:	KM DB-Assistant, KM Scanner File Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities

FAX / NETWORK FAX: FAX SYSTEM (G)

Compatibility:	Super G3
Transmission Speed:	Approximately 3 seconds per pages
Modem Speed:	33.6 Kbps with Auto fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Std 8MB / Max 16MB
Driver:	KM Network Fax Driver
Utilities:	Address Book for Network Fax
Additional Features:	Duplex TX/RX, Confidential RX/TX, Polling, Broadcasting, 2in1 RX

ADDITIONAL OPTIONS: Fax memory for Ultra Fine (FM1-8MB), Barcode Reader (BC-1)



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

A Division of Kyocera Mita America, Inc.
225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2003 Kyocera Mita America, Inc.
www.copystar.com

