

# FS-C8026N-A / FS-C8026N-B Specifications

## BASIC SPECIFICATIONS:

Configuration:	Color Tandem Network Printer with Standard Duplex, 150 Sheet Multi-Purpose Tray, and Optional Finishing. Standard with either Paper configuration: <b>Type A:</b> 3,000 Sheets (500/1,000/1,500) <b>Type B:</b> 1,500 Sheets (500 x 3)
Resolution:	600 x 600 DPI
Printer Memory:	Standard 512MB, via 168 pin DIMMs. Standard 20GB HDD and Compact Flash Card Slot (Type 1).
Electrical Requirements:	120V, 60Hz, 12.5A
Dimensions:	<b>Type A and B:</b> 27.5"W x 28.1"D x 35.3"H
Weight:	<b>Type A:</b> 299.3 lbs <b>Type B:</b> 277.3 lbs
Max Duty Cycle:	100,000 Pages per month

## CONTROLLER SPECIFICATIONS:

CPU/MHz:	PowerPC750CXe/600 MHz
Supported PDL / Emulations:	PRESCRIBE, KPDL3(PFS), PCL 6 (PCL 5c/5e/XL), KC-GL (HP-GL/2)
Fonts:	136 Outline Fonts for KPDL3, 80 Outlines Fonts for PCL 5c/5e/XL, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/Me/NT4.x/2000/XP
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100 BaseTX, Bi-Directional Parallel IEEE1284
KUIO LV Expansion Slot (1):	Optional IB-11 Serial RS-232C; IB-20 10/100 BaseTX, 10Base2; IB-22 Enhanced Wireless NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Client, PDF Direct Print, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

## OUTPUT SPEEDS:

Warm-Up Time:	Less than 179 Seconds
First Print Out Color:	9 Seconds or Less
First Print Out Monochrome:	9 Seconds or Less
Pages Per Minute (Color / Mono)*:	26 / 26 Letter, 13 / 13 Legal, 11 / 11 Ledger

\*Speed may vary depending on coverage.

## PAPER SUPPLY:

Standard Paper Sources:	150 Sheet MPT with either configuration: <b>Type A:</b> 3,000 (500/1,000/1,500) <b>Type B:</b> 1,500 (500 x 3)
Drawer Paper Size:	8.5" x 11", 8.5" x 14", 11" x 17", A4, A5, B5 <b>Type A:</b> 5.5" x 8.5" - 11" x 17" (1 Drawer), 8.5" x 11" (2 Drawers) <b>Type B:</b> 5.5" x 8.5" - 11" x 17" (3 Drawers)
MPT Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14", A4, A5, B5, Custom (2.8" x 5.8" - 12" x 18")
Paper Capacity:	<b>Type A:</b> 3,150 Sheets, <b>Type B:</b> 1,650 Sheets
Paper Weight:	16 - 28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

## DUPLEX UNIT:

Paper Size:	5.5" x 8.5" - 11" x 17", A3, A4, A4R, A5, A5R, B4, B5, B5R
Paper Weight:	16 - 28 lb Bond

## FINISHING OPTIONS:

### 3,000 SHEET STAPLE FINISHER: DF-610

Stack Capacity:	Main Tray: 3,000 Sheets; Sub Tray: 200 Sheets
Paper Size:	Main: 8.5"x11"-11"x17"; Sub: 5.5" x 8.5"-11"x17"
Paper Weight:	Main: 16lb Bond - 90lb Index; Sub: 16lb Bond - 110lb Index
Staple Capacity:	50 Sheets: 5.5" x 8.5", 8.5" x 14", 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	4 Positions: Top Left, Bottom Left, Two Left, Two Center
Saddle Stitch:	8.5" x 11", 11" x 17", Up to 16 Sheets
Dimensions / Weight:	31.4"W x 25.2"D x 37.4"H / 172 lbs

### PUNCH UNIT: PH-3

Paper Size:	8.5" x 11" - 11" x 17"
Number of Holes:	2 and 3
Weight:	8 lbs

### MULTI TRAY: MT-1

Number of Trays:	5
Capacity:	150 sheets (8.5" x 11") Per Tray
Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	13 - 43 lb
Dimensions / Weight:	14.5"W x 15.5"D x 22.6"H / 33 lbs

### BOOKLET FOLDER: BF-1

Folding Capacity:	1 - 16 Sheets
Capacity:	1 - 5 Sheets - 40 Booklets; 6 - 10 Sheets - 24 Booklets; 11 - 16 Sheets - 15 Booklets
Paper Size:	8.5" x 11", 11" x 17"
Paper Weight:	16 - 110 lb, Over 20 lb is one sheet only
Dimensions / Weight:	23.3"W x 17"D x 10"H / 42 lbs

## ADDITIONAL OPTIONS:

500 Sheet Face-Up Tray (PT-640)

## CONSUMABLES:

TK-812K:	Black Toner 20,000 Pages @ 5% Coverage*
TK-812Y:	Yellow Toner 20,000 Pages @ 5% Coverage*
TK-812M:	Magenta Toner 20,000 Pages @ 5% Coverage*
TK-812C:	Cyan Toner 20,000 Pages @ 5% Coverage*

\* ships with 6,000 Pages @ 5% Toner



Specifications and design are subject to change without notice. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc.  
225 Sand Road, PO Box 40008,  
Fairfield, NJ 07004-0008, USA  
©2004 Kyocera Mita America, Inc.  
[www.kyoceramita.com/us](http://www.kyoceramita.com/us)

